Energy Meter

Template Category	Electrical Energy Meter			
Template Version	С			
Category Description	Device for measuring quantity of energy use			
Classification System				
Classification	Three-phase energy meter with S0 interface			
Suitability for Use	Consultation - draft use only			
Template Custodian	CIBSE			
,	Parameter Name	Value	Units	Notes
Manufactur Specifications	Manufacturer	Saia-Burgess Controls AG	Text	
Specifications Specifications	Manufacturer Website Product Range	http://www.saia-pcd.com Energy meters	URL Text	
Specifications Specifications	Product Model Number CE Approval	ALE3D5F10KB2A00 Yes	Text Text	Or Code Number, Yes, No
Specifications	Product Literature	http://www.sbc-support.com	URL	
Specifications	Features	Three-phase energy meter with LCD display S0 interface, Imax = 65 A, 1 tariff, unidirectional, display of active power	Text	Free text to describe product
Construction			l	Title 000: 6 11 41 6 11 711 11 11 6 100T
Specifications Specifications	Type Mounting	Plastic encased electronic device 35 mm DIN hat rail	Text Text	This is a COBie field, other fields will be required in final PDTs This is a COBie field, other fields will be required in final PDTs
Specifications Specifications	Shape Material	Rectangle Housing lower part: Anjalon PC-J-150 GF30	Text Text	This is a COBie field, other fields will be required in final PDTs This is a COBie field, other fields will be required in final PDTs
•		Housing upper part: Lexan 940A-215155		
Specifications	Colour	Housing lower part: Light grey Housing upper part: blue transparent	Text	This is a COBie field, other fields will be required in final PDTs
Specifications Application	Finish	Matt	Text	This is a COBie field, other fields will be required in final PDTs
Specifications	Read out type	digital	Text	
Specifications Specifications	Remote reading Reference Standard	Y EN50470-3, IEC62053-21	Y/N Text	
Specifications Specifications	Certifications Measurement type	- Direct, unidirectional	Text	European Union's Measurement Instrument Directive (MID)
Specifications	Interface for remote reading	S0 interface	Text Text	
Dimensiona Specifications	Overall Length	82.00	Imm	Or Diameter. Minimum and maximum lengths available
Specifications	Overall Width	70.00	mm	Minimum and maximum widths available
Specifications Specifications	Overall Height Gross Weight	62.00 0.21	kg	Minimum and maximum heights available Equates to Operating Weight
Specifications Specifications	Shipping Weight Access Clearance Top	0.23 20.00		Equates to dry weight of unit plus packaging allowance Access required for maintenance of this item
Specifications	Access Clearance Bottom	20.00	mm	Access required for maintenance of this item
Specifications Specifications	Access Clearance Left Access Clearance Right	0.00	mm mm	Access required for maintenance of this item Access required for maintenance of this item
Specifications Specifications	Access Clearance Front Access Clearance Rear	0.00 0.00	mm mm	Access required for maintenance of this item Access required for maintenance of this item
Performance		0.00	J	Access required for maintenance of this item
Specifications Specifications	Reference Current Minimum Current	10 0.04		
Specifications	Maximim Current	65	Α	Olaca D. 40/
Specifications Specifications	Accuracy Ambient Operation Limits Temperature	1 −25…+55 °C	Percentage Degrees C	Class B = 1% To be entered as a range value. i.e10,+40
Specifications Flectrical D	Ambient Operating Limits Humidity Pata (if required)	575% r.H.	Percentage	To be entered as a range value. i.e. 0,90
Specifications Electrical D	Battery Supply	N	Y/N	
Specifications Specifications	Battery Type Incoming Supply Electrical Voltage	N/A 230	Text Volts	e.g. Alkaline, Lithium Ion Rechargeable
Specifications	Incoming Supply Phase	3	Number	1,3
Specifications Specifications	Incoming Supply Electrical Frequency Enclosure Rating	50 Hz IP51	Hertz Text	eg. N/A, DC, 50,60, Other, UserDefined IP rating
Specifications Specifications	Maximum Power Consumption Connection Size - main circuit	0.4	VA	
Specifications Specifications	Connection Size - main circuit Connection Size - communication	16 2.5	mm2 mm2	
Controls	Meter range	00'000,0099'999,99	Text	Counting from to
Specifications		100'000,0999'999,9		
Specifications Specifications	Display - digits Display - size	6	Number Number	Count of digits Heigh
Specifications	Pulses per kWh	1000	Number	Pulses showed at the display
	Embodied Carbon		kgCO2	AWAITING INDUSTRY STANDARD
Sustainable Material BREEAM etc Sustainable Material BREEAM etc	Life Cycle Analysis Location of Manufacturer	46° 55′ 31.28″ North, 7° 6′ 51.53″ East	Number GridRef	AWAITING INDUSTRY STANDARD AWAITING INDUSTRY STANDARD
Sustainable Material BREEAM etc	Green Guide for Specification	TO GO GILLO HORRI, I G GILGO LASE	Text	AWAITING INDUSTRY STANDARD
Sustainable Material BREEAM etc Sustainable Material BREEAM etc	Environmental Product Declaration Responsible Sourcing of Materials		Text Text	3rd Party Verification or Self Verification with URL to document AWAITING INDUSTRY STANDARD
Sustainable Material ETL	Energy Technology List		URL	Hyperlink to ETL webpage for product or N/A
Sustainable Material LEED v.4 Sustainable Material LEED v.4	Responsible Extraction of Materials Material Ingredient Reporting		Text Text	AWAITING INDUSTRY STANDARD AWAITING INDUSTRY STANDARD
Sustainable Material BREEAM etc	RoHS compliant		Y/N	
	WEE compliant & Maintenance		Y/N	
Facilities/Asset Management Facilities/Asset Management	O&M Manual Daily	https://www.sbc-support.com n/a	URL Text	Hyperlink to Manufacturer O&M Data Maintenance tasks or SFG2012 codes
Facilities/Asset Management	Weekly	n/a	Text	Maintenance tasks or SFG2012 codes
Facilities/Asset Management Facilities/Asset Management	Monthly Quarterly	n/a n/a	Text Text	Maintenance tasks or SFG2012 codes Maintenance tasks or SFG2012 codes
Facilities/Asset Management	6 Monthly	n/a n/a	Text	Maintenance tasks or SFG2012 codes Maintenance tasks or SFG2012 codes
Facilities/Asset Management Facilities/Asset Management	Annually Bespoke Timeframe	n/a	Text Text	Maintenance tasks or SFG2012 codes
Facilities/Asset Management Facilities/Asset Management	Maintenance Required 0-300hrs Maintenance Required 301-600hrs	n/a n/a	Text Text	Maintenance tasks required during this time frame Maintenance tasks required during this time frame
Facilities/Asset Management	Maintenance Required 601-1000hrs	n/a	Text	Maintenance tasks required during this time frame
Facilities/Asset Management Facilities/Asset Management	Maintenance Required 1001-2000hrs Maintenance Required 2001-4000hrs	n/a n/a	Text Text	Maintenance tasks required during this time frame Maintenance tasks required during this time frame
Facilities/Asset Management Facilities/Asset Management	Maintenance Required 40001-8000hrs Maintenance Required 8001-12000hrs	n/a n/a	Text Text	Maintenance tasks required during this time frame Maintenance tasks required during this time frame
Facilities/Asset Management Facilities/Asset Management	Expected Life Warranty ID	2 Year from invoice date, max. 30 month from date code.	Years Text	· •
This spreadsheet is the property of CIBS	E although it can be freely used in the ways described, and completed with data specific to particular products.			