

Product Data Template

Template Category	Controller - Human machine interface			
Template Version	a			
Category Description	Displays			
Classification System				
Classification	Web panel with embedded Micro-Browser, Base line 5.0" TFT WVGA			
Suitability for Use	Created			
Template Custodian	BCIA			
Information Category	Parameter Name	Value	Units	Notes
Manufacturer Data				
Specifications	Manufacturer	Saia-Burgess Controls AG	Text	
Specifications	Manufacturer Website	http://www.saia-pcd.com	URL	
Specifications	Product Range	Web Panel MB	Text	
Specifications	Product Model Number	PCD7.D450WTPF	Text	Or Code
Specifications	CE Approval	Yes	Text	Number, Yes, No
Specifications	Product Literature	http://www.sbc-support.com	URL	
Specifications	Features	Base line 5.0" TFT WVGA, 800 x 480 pixels, 65'536 colours with touch screen, transmissive LED backlight, 128 MByte on-board file system, FTP server, Ethernet TCP/IP, for front panel flush mounting	Text	Free text to describe product
Construction Data				
Specifications	Type	Plastic/metal encased electronic device	Text	This is a COBie field, other fields will be required in final PDTs
Specifications	Shape	Rectangle	Text	This is a COBie field, other fields will be required in final PDTs
Specifications	Material	Baseplate: Hot-dip galvanised sheet (DX51D+AZ150 or SVZ DX51D+Z275) Front Frame: Lexan EXL9330	Text	This is a COBie field, other fields will be required in final PDTs
Specifications	Colour	Baseplate: common tin Front Frame: light grey (RAL7035)	Text	This is a COBie field, other fields will be required in final PDTs
Specifications	Finish	Matt	Text	This is a COBie field, other fields will be required in final PDTs
Application				
Specifications	Reference Standard	UL	Text	
Specifications	Certifications	CE	Text	
Specifications	Measurement type	N/A	Text	
Specifications	Interface for remote reading	USB & Ethernet	Text	Types of communication ports
Dimensional Data				
Specifications	Overall Depth	45.60	mm	Or Diameter. Minimum and maximum lengths available
Specifications	Overall Width	166.00	mm	Minimum and maximum widths available
Specifications	Overall Height	126.00	mm	Minimum and maximum heights available
Specifications	Gross Weight	0.48	kg	Equates to Operating Weight
Specifications	Shipping Weight	0.48	kg	Equates to dry weight of unit plus packaging allowance
Specifications	Access Clearance Top	20.00	mm	Access required for maintenance of this item
Specifications	Access Clearance Bottom	20.00	mm	Access required for maintenance of this item
Specifications	Access Clearance Left	20.00	mm	Access required for maintenance of this item
Specifications	Access Clearance Right	20.00	mm	Access required for maintenance of this item
Specifications	Access Clearance Front	0.00	mm	Access required for maintenance of this item
Specifications	Access Clearance Rear	50.00	mm	Access required for maintenance of this item
Performance Data				
Specifications	Diagonal		5	Inch
Specifications	Resolution	WVGA		
Specifications	Resolution	800 x 480		pixel
Specifications	Colours	65536		Number
Specifications	Ambient Operation Limits Temperature	0...+50 °C		Degrees C
Specifications	Ambient Operating Limits Humidity	10...80% r.H.		Percentage
Electrical Data (if required)				
Specifications	Battery Supply	N		Y/N
Specifications	Battery Type	N/A		Text
Specifications	Incoming Supply Electrical Voltage	24		Volts
Specifications	Incoming Supply Tolerance	+/- 20		%
Specifications	Incoming Supply Type	DC		Text
Specifications	Enclosure Rating	IP65		Text
Specifications	Maximum Power Consumption	8.4 / 350		W / mA
Specifications	Connection Size - main circuit	n/a		mm2
Specifications	Connection Size - communication	n/a		mm2
Controls				
Specifications	Backlight	LED		Number
Specifications	Touch screen	Resistive		Number
Specifications	Real Time Clock	Yes		Text
Specifications	Cut-out	157 * 117		Number
Sustainability				
Sustainable Material BREEAM etc	Embodied Carbon			kgCO2
Sustainable Material BREEAM etc	Life Cycle Analysis			Number
Sustainable Material BREEAM etc	Location of Manufacturer	46° 55' 31.28" North, 7° 6' 51.53" East		GridRef
Sustainable Material BREEAM etc	Green Guide for Specification			Text
Sustainable Material BREEAM etc	Environmental Product Declaration			Text
Sustainable Material BREEAM etc	Responsible Sourcing of Materials			Text
Sustainable Material ETL	Energy Technology List			URL
Sustainable Material LEED v.4	Responsible Extraction of Materials			Text
Sustainable Material LEED v.4	Material Ingredient Reporting			Text
Sustainable Material BREEAM etc	RoHS compliant			Y/N
Sustainable Material BREEAM etc	WEE compliant			Y/N
Operations & Maintenance				
Facilities/Asset Management	O&M Manual	https://www.sbc-support.com		URL
Facilities/Asset Management	Daily	n/a		Text
Facilities/Asset Management	Weekly	n/a		Text
Facilities/Asset Management	Monthly	n/a		Text
Facilities/Asset Management	Quarterly	n/a		Text
Facilities/Asset Management	6 Monthly	n/a		Text
Facilities/Asset Management	Annually	n/a		Text
Facilities/Asset Management	Bespoke Timeframe	n/a		Text
Facilities/Asset Management	Maintenance Required 0-300hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 301-600hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 601-1000hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 1001-2000hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 2001-4000hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 4001-8000hrs	n/a		Text
Facilities/Asset Management	Maintenance Required 8001-12000hrs	n/a		Text
Facilities/Asset Management	Expected Life			Years
Facilities/Asset Management	Warranty ID	2 Year from invoice date, max. 30 month from date code.		Text

This spreadsheet is the property of CIBSE although it can be freely used in the ways described, and completed with data specific to particular products.