

Controller **Template Category** Template Version а Category Description Saia PCD® modular programmable controllers **Classification System** Classification Remote data points Saia PCD® Provisional Suitability for Use BCIA **Template Custodian Parameter Name** Information Category Value Units Notes Manufacturer Data Manufacturer Saia-Burgess Controls AG **Specifications** Text Manufacturer Website URL **Specifications** http://www.saia-pcd.com Remote input/output stations with 4 I/O module slots **Specifications** Product Range Text **Specifications** Product Model Number PCD3.T666 Text Or Code CE Approval Text Number, Yes, No **Specifications** Yes URL **Specifications** Product Literature http://www.sbc-support.com Smart-RIO, Ether-S-IO data exchange, programmable, 128 KByte program **Specifications** memory, up to 256 I/O, 2 Interrupts, web server and on-board RS-485 Features Text Free text to describe product interface **Construction Data** Plastic encased electronic device This is a COBie field, other fields will be required in final PDTs **Specifications** Гуре Text Specifications Mounting 35 mm DIN hat rail Text This is a COBie field, other fields will be required in final PDTs This is a COBie field, other fields will be required in final PDTs **Specifications** Shape Rectangle Text This is a COBie field, other fields will be required in final PDTs **Specifications** Material Text Plastic This is a COBie field, other fields will be required in final PDTs **Specifications** Colour _ight Grey Text Finish Text This is a COBie field, other fields will be required in final PDTs **Specifications** Matt Enclosure Rating **Specifications** Text IP rating Application Reference Standard **Specifications** requested Text **Specifications** Certifications CE Text **Dimensional Data** Overall Depth 139.00 mm Or Diameter. Minimum and maximum lengths available **Specifications** 130.00 mm Overall Width Minimum and maximum widths available **Specifications** 100.50 **Specifications** Overall Height mm Minimum and maximum heights available Gross Weight 0.82 kg Equates to Operating Weight **Specifications** Specifications Shipping Weight Equates to dry weight of unit plus packaging allowance kg **Specifications** Access Clearance Top 20.00 mm Access required for maintenance of this item **Specifications** Access Clearance Bottom 20.00 mm Access required for maintenance of this item Access Clearance Left 0.00 mm Access required for maintenance of this item **Specifications** 0.00 mm **Specifications** Access Clearance Right Access required for maintenance of this item 20.00 mm Access Clearance Front **Specifications** Access required for maintenance of this item 0.00 mm Access Clearance Rear **Specifications** Access required for maintenance of this item **Performance Data** Ambient Storage Limits Temperature –40…+70 °C Degrees C **Specifications** +0...+55 °C Ambient Operation Limits Temperature Degrees C **Specifications** Ambient Operating Limits Humidity Percentage **Specifications**

Altitude Electrical Data (if required)

Specifications

Electrical	Data (in required)			
Specifications	Supply voltage	24 VDC -20%/+20%	Volts	
pecifications	Current consumption		A	
pecifications	Power consumption	typ. 15 W	W	
Controls				
pecifications	On-Board I/Os		0 Number	
pecifications	Max. I/Os		256 Number	
pecifications	Max. Interfaces		11 Number	
Sustainat				
Istainable Material BREEAM etc	Embodied Carbon		kgCO2	AWAITING INDUSTRY STANDARD
ustainable Material BREEAM etc	Life Cycle Analysis		Number	AWAITING INDUSTRY STANDARD
ustainable Material BREEAM etc	Location of Manufacturer	46° 55' 31.28" North, 7° 6' 51.53" East	GridRef	AWAITING INDUSTRY STANDARD
ustainable Material BREEAM etc	Green Guide for Specification		Text	AWAITING INDUSTRY STANDARD
ustainable Material BREEAM etc	Environmental Product Declaration		Text	3rd Party Verification or Self Verification with URL to document
ustainable Material BREEAM etc	Responsible Sourcing of Materials		Text	AWAITING INDUSTRY STANDARD
Istainable Material ETL	Energy Technology List		URL	Hyperlink to ETL webpage for product or N/A
ustainable Material LEED v.4	Responsible Extraction of Materials		Text	AWAITING INDUSTRY STANDARD
ustainable Material LEED v.4	Material Ingredient Reporting		Text	AWAITING INDUSTRY STANDARD
Istainable Material BREEAM etc	RoHS compliant		Y/N	
ustainable Material BREEAM etc	WEE compliant		Y/N	
	s & Maintenance			
acilities/Asset Management	O&M Manual	https://www.sbc-support.com	URL	Hyperlink to Manufacturer O&M Data
cilities/Asset Management	Daily	n/a	Text	Maintenance tasks or SFG2012 codes
cilities/Asset Management	Weekly	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	Monthly	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	Quarterly	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	6 Monthly	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	Annually	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	Bespoke Timeframe	n/a	Text	Maintenance tasks or SFG2012 codes
acilities/Asset Management	Maintenance Required 0-300hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 301-600hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 601-1000hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 1001-2000hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 2001-4000hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 40001-8000hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Maintenance Required 8001-12000hrs	n/a	Text	Maintenance tasks required during this time frame
acilities/Asset Management	Expected Life		Years	
acilities/Asset Management	Warranty ID	2 Year from invoice date, max. 30 month from date code.	Text	

sea level

This spreadsheet is the property of CIBSE although it can be freely used in the ways described, and completed with data specific to particular products.